



SPECIFICATIONS
 Current Rating: 0.5A AC,DC
 Voltage Rating: 30V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 100MΩ Min.
 Withstanding Voltage: 200V AC/minute
 Pin Material: Phosphor Bronze/Tin or gold-plated
 Solder Tabs: Phosphor Bronze/Tin or gold-plated
 Material: Nylon or LCP , UL94V-0
 Color: Natural(Beige)

PART NO.	Dimensions		
	A	B	C
SCT0800WR-S-02P	0.80	3.80	1.82
SCT0800WR-S-03P	1.60	4.60	2.62
SCT0800WR-S-04P	2.40	5.40	3.42
SCT0800WR-S-05P	3.20	6.20	4.22
SCT0800WR-S-06P	4.00	7.00	5.02
SCT0800WR-S-07P	4.80	7.80	5.82
SCT0800WR-S-08P	5.60	8.60	6.62
SCT0800WR-S-09P	6.40	9.40	7.42
SCT0800WR-S-10P	7.20	10.20	8.22
SCT0800WR-S-11P	8.00	11.00	9.02
SCT0800WR-S-12P	8.80	11.80	9.82
SCT0800WR-S-13P	9.60	12.60	10.62
SCT0800WR-S-14P	10.40	13.40	11.42
SCT0800WR-S-15P	11.20	14.20	12.22
SCT0800WR-S-18P	13.60	16.60	14.62
SCT0800WR-S-20P	15.20	18.20	16.22
SCT0800WR-S-24P	18.40	21.40	19.42

OPERATION	~ 10	±0.15	DRAW	YANG	2016.01.25	SCALE	
	20 ~ 30	±0.30	DESIGN			UNIT	mm
	30 ~	±0.50	CHECK	MICKY	2016.01.25	SIZE	A4
ANGLE		± 2'	APPROVE	ALLEN	2016.01.25	SHEET	1/1
TOL.			PROJ.			DRAWING NO.	SCT0800

底部增加两个扣点

NEW

MODIFICATION DESCRIPTION

CHANGE

APPROVE

APPROVE

DATE

DATE

DATE

DATE

DATE

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED

PART NO. SCT0800WR-S-XXP

TITLE: 0.8 IDC 90C SMT WF

DRAWING NO. SCT0800