



SPECIFICATIONS

Voltage rating: 50V AC, DC
 Current rating: 2A, AC, DC (AWG#28)
 Withstanding voltage: 500V AC/minute
 Insulation resistance: 100M Ω /min
 Temperature range: -40°C - +85°C
 Contact resistance: 20m Ω max

WAFER

Part No.: SCT1200WR-S-XXP
 Poles: 2-15
 Material: Nylon 9T, UL94V-0
 Contact: Brass, Tin plated

PART NO	DIMENSION			
	A	B	C	D
SCT1200WR-S-02	1.20	2.70	4.20	3.20
SCT1200WR-S-03	2.40	3.90	5.40	4.40
SCT1200WR-S-04	3.60	5.10	5.60	5.60
SCT1200WR-S-05	4.80	6.30	7.80	6.80
SCT1200WR-S-06	6.00	7.50	9.00	8.00
SCT1200WR-S-07	7.20	8.70	10.20	9.20
SCT1200WR-S-08	8.40	9.90	11.40	10.40
SCT1200WR-S-09	9.60	11.10	12.60	11.60
SCT1200WR-S-10	10.80	12.30	13.80	12.80
SCT1200WR-S-11	12.00	13.50	15.00	14.00
SCT1200WR-S-12	13.20	14.70	16.20	15.20
SCT1200WR-S-13	14.40	15.90	17.40	16.40
SCT1200WR-S-14	15.60	17.10	18.60	17.60
SCT1200WR-S-15	16.80	18.30	19.80	18.80

02PIN

PCB LAYOUT

03-15PIN

OPERATION	~ 10	±0.15	DRAW	Judy Huang	2006/05/02	SCALE	
DESIGN	20 ~ 30	±0.30	CHECK	Micky Liu	2006/05/02	UNIT	mm
Angle	30 ~	±0.50	APPROVE	Hellen Li	2006/05/02	SIZE	A4
DIM		± 2'				SHEET	1/1
TOL						TITLE:	ACH1.2 90C SMT Wafer
						DRAWING NO.	SCT1200

REV	0	05/12/27	NEW	MODIFICATION DESCRIPTION	CHANGE	APPROVE
DATE						

