




SPECIFICATIONS

Voltage rating: 150V AC, DC

Current rating: 1A, AC, DC (AWG#28)

Withstanding voltage: 500V AC/minute

Insulation resistance: 500M Ω min

Temperature range: -25°C - +85°C

Contact resistance: 30m Ω max

WAFER

Part No.: SCT1252WR-XXP

Material: Nylon 66, UL94V-0

Contact: Brass, Tin plated

Sloder Tabs: Phosphor Bronze, Tin plated

PART NO.	Dimensions	
	A	B
SCT1252WR-02P	1.25	3.75
SCT1252WR-03P	2.50	5.00
SCT1252WR-04P	3.75	6.25
SCT1252WR-05P	5.00	7.50
SCT1252WR-06P	6.25	8.75
SCT1252WR-07P	7.50	10.00
SCT1252WR-08P	8.75	11.25
SCT1252WR-09P	10.00	12.50
SCT1252WR-10P	11.25	13.75
SCT1252WR-11P	12.50	15.00
SCT1252WR-12P	13.75	16.25
SCT1252WR-13P	15.00	17.50
SCT1252WR-14P	16.25	18.75
SCT1252WR-15P	17.50	20.00

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	Judy.Huang	2006/05/02	SCALE	UNIT	mm	PART NO.	SCT1252WR-XXP
0	05/12/27	NEW			~ 10 ±0.15	DESIGN							
					20 ~ 30 ±0.30	CHECK	Micky.Liu	2006/05/02					
					30 ~ ±0.50	APPROVE	Hellen.Li	2006/05/02					
					Angle ± 2°								
					DIM TOL								



森康达电子有限公司
SCONDAR ELECTRONIC LIMITED

PART NO. SCT1252WR-XXP
TITLE: DF13 1.25 90C WAFER
DRAWING NO. SCT1252WR-XXP