



**SPECIFICATIONS**  
 Voltage rating: 100V AC, DC  
 Current rating: 1A, AC, DC  
 Withstanding voltage: 250V AC/minute  
 Insulation resistance: 100MΩ min  
 Temperature range: -25°C - +85°C  
 Contact resistance: 20mΩ max

**WAFER**  
 Part No.: SCT1254HA-XXP  
 Material: Nylon 66, UL94V-0  
 Circuits: 02-15, 20, 30  
 Mates With: SCT1254WRR00

PART NO.	Dimensions			
	A	B	C	D
SCT1254HA-02P	1.25	2.90	6.10	7.00
SCT1254HA-03P	2.50	4.15	7.35	8.25
SCT1254HA-04P	3.75	5.40	8.60	9.50
SCT1254HA-05P	5.00	6.65	9.85	10.75
SCT1254HA-06P	6.25	7.90	11.1	12.00
SCT1254HA-07P	7.50	9.15	12.35	13.25
SCT1254HA-08P	8.75	10.40	13.60	14.50
SCT1254HA-09P	10.00	11.65	14.85	15.75
SCT1254HA-10P	11.25	12.90	16.10	17.00
SCT1254HA-11P	12.50	14.15	17.35	18.25
SCT1254HA-12P	13.75	15.40	18.60	19.50
SCT1254HA-14P	16.25	17.90	21.10	22.00
SCT1254HA-15P	17.50	19.15	22.35	23.25
SCT1254HA-20P	23.75	25.40	28.60	29.50
SCT1254HA-30P	36.25	37.90	41.10	42.00

OPERATION	~ 10	±0.15	DRAW	LYLE	2019/03/15	SCALE	
	20 ~ 30	±0.30	DESIGN			UNIT	mm
	30 ~	±0.50	CHECK	L.S.A.L	2019/03/15	SIZE	A4
Angle			APPROVE	ALLEN	2019/03/15	SHEET	1/1
DIM						PROJ.	
TOL						DRAWING NO.	SCT1254

**SCONDAR** 森康达电子有限公司  
 SCONDAR ELECTRONIC LIMITED

PART NO. SCT1254HA-XXP  
 TITLE: 1.25 Hook housing  
 DRAWING NO. SCT1254

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE
0		NEW		
1				