



**SPECIFICATIONS**  
 Voltage Rating: 100V AC/DC  
 Current Rating: 2A AC/DC  
 Withstanding Voltage: 800V AC/minute  
 Insulation Resistance: 1,000MΩ min.  
 Temperature Range: -25° C - +85° C  
 Contact Resistance: 20mΩ max

**HOUSING**  
 Part No: SCT2001H-XXP  
 Poles: 2-16  
 Material: Nylon 66, UL94V-2

PART NO	DIMENSION		
	A	B	C
SCT2001H-02	2.00	4.80	5.80
SCT2001H-03	4.00	6.80	7.80
SCT2001H-04	6.00	8.80	9.80
SCT2001H-05	8.00	10.80	11.80
SCT2001H-06	10.00	12.80	13.80
SCT2001H-07	12.00	14.80	15.80
SCT2001H-08	14.00	16.80	17.80
SCT2001H-09	16.00	18.80	19.80
SCT2001H-10	18.00	20.80	21.80
SCT2001H-11	20.00	22.80	23.80
SCT2001H-12	22.00	24.80	25.80
SCT2001H-13	24.00	26.80	27.80
SCT2001H-14	26.00	28.80	29.80
SCT2001H-15	28.00	30.80	31.80
SCT2001H-16	30.00	32.80	33.80

**SCONDAR** 森康达电子有限公司  
 SCONDAR ELECTRONIC LIMITED

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	SCALE	PART NO.	TITLE:	DRAWING NO.
0	05/12/27	NEW			~ 10 ±0.15 20 ~ 30 ±0.30 30 ~ ±0.50 Angle DIM ± 2'	DESIGN CHECK	mm A4 1/1	SCT2001H-XXP	PH2.0 HOUSING	SCT2001
1										

