



SPECIFICATIONS
 Voltage Rating: 100V AC/DC
 Current Rating: 2A AC/DC
 Withstanding Voltage: 800V AC/minute
 Insulation Resistance: 1,000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

TERMINAL

Part No: SCT2001T
 Wire Range: AWG#22-#28 (OD1.5mm)
 Material: Phos. Bronze
 Finish: Tin Plated
 Thickness: 0.2mm
 Q'TY: 10, 000PCS/Reel

OPERATION		~ 10	±0.15	DRAW	Judy.Huang	2006/05/02	SCALE	UNIT	mm	
DESIGN		20 ~ 30	±0.30		Judy.Huang	2006/05/02		SIZE	A4	
CHECK		30 ~	±0.50	CHECK	Micky.Liu	2006/05/02	SHEET	1/1	PART NO.	SCT2001T
APPROVE		Angle	± 2'	APPROVE	Hellen.Li	2006/05/02	PROJ.	DRAWING NO.	PH2.0 TERMINAL	
CHANGE		DM	TOL.	APPROVE					SCT2001	
REV	DATE	MODIFICATION DESCRIPTION		CHANGE	APPROVE					
0	05/12/27	NEW								
1										

SCONDAR
 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED