



**SPECIFICATIONS**

Voltage Rating: 100V AC/DC  
 Current Rating: 2A AC/DC  
 Withstanding Voltage: 800V AC/minute  
 Insulation Resistance: 1,000MΩ min.  
 Temperature Range: -25° C - +85° C  
 Contact Resistance: 20mΩ max

**WAFER**

Part No: SCT2001WR-S-XXP  
 Poles: 2-16  
 Material: Nylon 9T, UL94V-0  
 Pin: Brass, Tin plated

PART NO.	Dimensions	
	A	B
SCT2001WR-S-2P	2.00	8.00
SCT2001WR-S-3P	4.00	10.00
SCT2001WR-S-4P	6.00	12.00
SCT2001WR-S-5P	8.00	14.00
SCT2001WR-S-6P	10.00	16.00
SCT2001WR-S-7P	12.00	18.00
SCT2001WR-S-8P	14.00	20.00
SCT2001WR-S-9P	16.00	22.00
SCT2001WR-S-10P	18.00	24.00
SCT2001WR-S-11P	20.00	26.00
SCT2001WR-S-12P	22.00	28.00
SCT2001WR-S-13P	24.00	30.00
SCT2001WR-S-14P	26.00	32.00
SCT2001WR-S-15P	28.00	34.00
SCT2001WR-S-16P	30.00	36.00

**SCONDAR** 森康达电子有限公司  
 SCONDAR ELECTRONIC LIMITED

OPERATION	DRAW	CHEENNA	SCALE
~ 10 ±0.15	DESIGN	09-09TH/09Y	mm
20 ~ 30 ±0.30	CHECK		SIZE A4
30 ~ Angle ±0.50	MICKY	09-09TH/09Y	SHEET 1/1
DIM ± z	APPROVE	09-09TH/09Y	PROJ.

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	SCALE	DRAWING NO.
0	05/12/27	NEW				SCT2001WR-S
1						PH2.0 90C SMT WAFER