



SPECIFICATIONS
 Voltage Rating: 250V AC/DC
 Current rating: 2A AC/DC
 Withstanding Voltage: 800V AC/minute
 Insulation resistance: 1,000MΩmin
 Temperature range: -25° C- +85° C
 Contact Resistance: 20mΩ max

TERMINAL
 Part NO: SCT2003TRB
 Thickness: 0.20mm
 Wire Range: AWG#24-#28 (OD1.5mm)
 Material: Brass, Tin Plated
 Hardness: H/EH
 Reel Q'ty: 10000pcs

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED

OPERATION		~ 10	±0.15	DRAW	Judy.Huang	2006/05/02	SCALE	mm
DESIGN		20 ~ 30	±0.30	CHECK	Micky.Liu	2006/05/02	UNIT	A4
ANGLE		30 ~	±0.50	APPROVE	Hellen.Li	2006/05/02	SHEET	1/1
DIM		± 2'					PROJ.	◆
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE			PART NO.	SCT2003TRB
0	05/12/27	NEW					TITLE:	SAN2.0 90C TERMINAL
1							DRAWING NO.	SCT2003