



PCB LAYOUT

SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 3A AC/DC
 Withstanding Voltage: 800V AC/minute
 Insulation Resistance: 1,000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING

Part No: SCT2004WR-2xXXP
 Poles: 2x2-17
 Material: Nylon 66, UL94V-2
 Pin: Brass, Tin plated

PART NO.	Dimension	
	A	B
SCT2004WR-2X2P	6.00	2.00
SCT2004WR-2X3P	8.00	4.00
SCT2004WR-2X4P	10.00	6.00
SCT2004WR-2X5P	12.00	8.00
SCT2004WR-2X6P	14.00	10.00
SCT2004WR-2X7P	16.00	12.00
SCT2004WR-2X8P	18.00	14.00
SCT2004WR-2X9P	20.00	16.00
SCT2004WR-2X10P	22.00	18.00
SCT2004WR-2X11P	24.00	20.00
SCT2004WR-2X12P	26.00	22.00
SCT2004WR-2X13P	28.00	24.00
SCT2004WR-2X14P	30.00	26.00
SCT2004WR-2X15P	32.00	28.00
SCT2004WR-2X16P	34.00	30.00
SCT2004WR-2X17P	36.00	32.00

OPERATION	~ 10	±0.15	DRAW	Judy.Huang	2006/05/02	SCALE	
DESIGN	20 ~ 30	±0.30	CHECK	Micky.Liu	2006/05/02	UNIT	mm
Angle	30 ~	±0.50	APPROVE	Hellen.Li	2006/05/02	SIZE	A4
DIM		± 2'				SHEET	1/1
TOL						PROJ.	◆
DATE	05/12/27		CHANGE			DRAWING NO.	SCT2004WR
REV	0		DESCRIPTION	NEW		TITLE:	PHD2.0 90C WAFER

SGT 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED