



NOTES:

PART NO. : SCT2004WV-2*NP
 Current Rating: 2A AC, DC
 Voltage Rating: 250V AC, DC
 Temperature Range: $-25^{\circ}C \pm 85^{\circ}C$
 Contact Resistance: 20m max
 Insulation Resistance: 1000M min
 Withstanding Voltage: 800V AC/minute
 Material: PA66 UL 94V-2

PART NO.	Dimensions	
	A	B
SCT2004-WV-2X2P	6.00	2.00
SCT2004-WV-2X3P	8.00	4.00
SCT2004-WV-2X4P	10.00	6.00
SCT2004-WV-2X5P	12.00	8.00
SCT2004-WV-2X6P	14.00	10.00
SCT2004-WV-2X7P	16.00	12.00
SCT2004-WV-2X8P	18.00	14.00
SCT2004-WV-2X9P	20.00	16.00
SCT2004-WV-2X10P	22.00	18.00
SCT2004-WV-2X11P	24.00	20.00
SCT2004-WV-2X12P	26.00	22.00
SCT2004-WV-2X13P	28.00	24.00
SCT2004-WV-2X14P	30.00	26.00
SCT2004-WV-2X15P	32.00	28.00
SCT2004-WV-2X16P	34.00	30.00
SCT2004-WV-2X17P	36.00	32.00

OPERATION	~ 10	± 0.15	DRAW	Judy-Huong	2006/05/02	SCALE	mm	 森康达电子有限公司 SCONDAR ELECTRONIC LIMITED
DESIGN	20 ~ 30	± 0.30	CHECK	Micky.Liu	2006/05/02	UNIT	A4	
ANGLE	30 ~	± 0.50	APPROVE	Hellen.Li	2006/05/02	SIZE	1/1	
DATE	MODIFICATION DESCRIPTION	CHANGE APPROVE	DIM	TOL	PROJ.	DRAWING NO.	SCT2004WV	
REV	DATE	MODIFICATION DESCRIPTION	CHANGE APPROVE	DIM	TOL	PROJ.	SCT2004WV	

1 2 3 4 5 6 7 8 9 10