



SPECIFICATIONS

Voltage Rating: 250V AC/DC

Current Rating: 3A AC/DC

Withstanding Voltage: 1000V AC/minute

Insulation Resistance: 1,000MΩ min.

Temperature Range: -25° C - +85° C

Contact Resistance: 20mΩ max

HOUSING

Part No: SCT2006H-XXP

Poles: 2-16

Material: Nylon 66, UL94V-0

PART NO.	Dimensions	
	A	B
SCT2006H-02P	2.00	4.60
SCT2006H-03P	4.00	6.60
SCT2006H-04P	6.00	8.60
SCT2006H-05P	8.00	10.60
SCT2006H-06P	10.00	12.60
SCT2006H-07P	12.00	14.60
SCT2006H-08P	14.00	16.60
SCT2006H-09P	16.00	18.60
SCT2006H-10P	18.00	20.60
SCT2006H-11P	20.00	22.60
SCT2006H-12P	22.00	24.60
SCT2006H-13P	24.00	26.60
SCT2006H-14P	26.00	28.60
SCT2006H-15P	28.00	30.60
SCT2006H-16P	30.00	32.60

					OPERATION	DRAW	CHENA	2009.11.03	SCALE		森康达电子有限公司 SCONDAR ELECTRONIC LIMITED	
					~ 10 ±0.15	DESIGN			UNIT	mm		
					20 ~ 30 ±0.30	CHECK	MICKY	2009.11.05	SIZE	A4	PART NO.	SCT2006H-XXP
0	05/12/27				30 ~ ±0.50	APPROVE	HELLEN	2009.11.08	SHEET	1/1	TITLE:	YH2.0 HOUSING
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	Angle ± 2'				PROJ.		DRAWING NO.	SCT2006
					DIM TOL							