



PART NO.	Dimensions	
	A	B
SCT2006WR-02P	2.00	6.00
SCT2006WR-03P	4.00	8.00
SCT2006WR-04P	6.00	10.00
SCT2006WR-05P	8.00	12.00
SCT2006WR-06P	10.00	14.00
SCT2006WR-07P	12.00	16.00
SCT2006WR-08P	14.00	18.00
SCT2006WR-09P	16.00	20.00
SCT2006WR-10P	18.00	22.00
SCT2006WR-11P	20.00	24.00
SCT2006WR-12P	22.00	26.00
SCT2006WR-13P	24.00	28.00
SCT2006WR-14P	26.00	30.00
SCT2006WR-15P	28.00	32.00
SCT2006WR-16P	30.00	34.00

SPECIFICATIONS
 Voltage Rating: 250V AC/DC
 Current Rating: 3A AC/DC
 Withstanding Voltage: 1000V AC/minute
 Insulation Resistance: 1,000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

WAFER
 Part No: SCT2006WR-XXP
 Poles: 2-16
 Material: Nylon 66, UL94V-0
 Pin: Brass, Tin plated

OPERATION	~ 10	±0.15	DRAW	QIU	2016-11-23	SCALE	
	20 ~ 30	±0.30	DESIGN			UNIT	mm
	30 ~	±0.50	CHECK	MICKY	2016-11-23	SIZE	A4
ANGLE	30 ~	±2°	APPROVE	HELLEN	2016-11-23	SHEET	1/1
DIM						PROU.	
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE		DRAWING NO.	
0	05/12/27	NEW					

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED

PART NO. SCT2006WR-XXP
 TITLE: YH2.0 90C WAFER

DRAWING NO. SCT2006