



PCB LAYOUT

SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 3A AC/DC
 Withstanding Voltage: 1000V AC/minute
 Insulation Resistance: 1,000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

WAFER

Part No: SCT2006WV-S-XXPB
 Poles: 2-16
 Material: Nylon 46, UL94V-0
 Pin: Brass, Tin plated

PART NO.	Dimensions			
	A	B	C	D
SCT2006WV-S-02P	2.00	4.75	8.00	2.80
SCT2006WV-S-03P	4.00	6.75	10.00	3.20
SCT2006WV-S-04P	6.00	8.75	12.00	3.50
SCT2006WV-S-05P	8.00	10.75	14.00	5.50
SCT2006WV-S-06P	10.00	12.75	16.00	7.50
SCT2006WV-S-07P	12.00	14.75	18.00	9.50
SCT2006WV-S-08P	14.00	16.75	20.00	11.50
SCT2006WV-S-09P	16.00	18.75	22.00	13.50
SCT2006WV-S-10P	18.00	20.75	24.00	15.50
SCT2006WV-S-11P	20.00	22.75	26.00	15.50
SCT2006WV-S-12P	22.00	24.75	28.00	15.50
SCT2006WV-S-13P	24.00	26.75	30.00	15.50
SCT2006WV-S-14P	26.00	28.75	32.00	15.50
SCT2006WV-S-15P	28.00	30.75	34.00	15.50
SCT2006WV-S-16P	30.00	32.75	36.00	15.50

OPERATION	SCALE	UNIT	SIZE	SHEET	PROJ.
~ 10 ±0.15	mm	A4	1/1	1/1	1/1
20 ~ 30 ±0.30					
30 ~ Angle ±0.50					
± 2' DIM TOL					

REV	DATE	MODIFICATION DESCRIPTION	CHANGE APPROVE	APPROVE	DATE
0	05/12/27	NEW			2009.11.05
1					2009.11.08

OPERATION	DRAW	CHENA	SCALE	TITLE	DRAWING NO.
DESIGN					
CHECK		MICKY			
APPROVE		HELLEN			

SCONDAR 森康达电子有限公司
SCONDAR ELECTRONIC LIMITED

SCT2006WV-S-XXPB
YH2.0 90C SMT WAFER
SCT2006