



PART NO.	Dimensions		
	A	B	C
SCT2007H-02P	2.00	6.00	6.00
SCT2007H-03P	4.00	8.00	8.00
SCT2007H-04P	6.00	4.00	10.00
SCT2007H-05P	8.00	6.00	12.00
SCT2007H-06P	10.00	8.00	14.00
SCT2007H-07P	12.00	10.00	16.00
SCT2007H-08P	14.00	12.00	18.00
SCT2007H-09P	16.00	14.00	20.00
SCT2007H-10P	18.00	16.00	22.00
SCT2007H-11P	20.00	18.00	24.00
SCT2007H-12P	22.00	20.00	26.00
SCT2007H-13P	24.00	22.00	28.00
SCT2007H-14P	26.00	24.00	30.00
SCT2007H-15P	28.00	26.00	32.00

**SPECIFICATIONS**  
 Voltage Rating: 100V AC/DC  
 Current Rating: 1A AC/DC  
 Withstanding Voltage: 800V AC/minute  
 Insulation Resistance: 1,000MΩ min.  
 Temperature Range: -25° C - +85° C  
 Contact Resistance: 20mΩ max

**HOUSING**  
 Part No: SCT2007H-XX  
 Poles: 2-16  
 Material: Nylon 66, UL94V-0

OPERATION	~ 10	±0.15	DRAW	Judy.Huang	2006/05/02	SCALE	mm	<b>森康达电子有限公司</b> SONDAR ELECTRONIC LIMITED	
DESIGN	20 ~ 30	±0.30	CHECK	Micky.Liu	2006/05/02	UNIT	A4		
ANGLE	30 ~	±0.50	APPROVE	Hellen.Li	2006/05/02	SHEET	1/1	PART NO.	SCT2007H-XXP
DIM	± 2'					PROJ.		TITLE:	AMP2.0 Housing
DATE	05/12/27	NEW	CHANGE			DRAWING NO.			SCT2007
REV	0	MODIFICATION DESCRIPTION	APPROVE						

1 2 3 4 5 6 7 8 9 10