



**SPECIFICATIONS**

Voltage Rating: 100V AC/DC  
 Current Rating: 1A AC/DC  
 Withstanding Voltage: 800V AC/minute  
 Insulation Resistance: 1, 000MΩ min.  
 Temperature Range: -25° C - +85° C  
 Contact Resistance: 20mΩ max

**TERMINAL**

Part No: SCT2007T  
 Wire Range: AWG#24-#28 (OD1. 5mm)  
 Material: Phos. Bronze  
 Finish: Tin Plated  
 Thickness: 0. 25mm  
 Q'TY: 10, 000PCS/Reel 1

OPERATION		DRAW		Judy-Huang		2006/05/02		SCALE	
~ 10		DESIGN						mm	
± 0.15		CHECK		Micky Liu		2006/05/02		A4	
20 ~ 30		APPROVE		Hellen.Li		2006/05/02		1/1	
± 0.30		CHANGE						DRAWING NO.	
30 ~		APPROVE						SCT2007T	
± 0.50		DIM		Angle		± 2'		PART NO.	
± 2'		TOL		TOL				SCT2007T	
REV		DATE		MODIFICATION DESCRIPTION		NEW		TITLE:	
0		05/12/27						AMP2.0 TERMINAL	
1								DRAWING NO.	
								SCT2007	

**SCONDAR** 森康达电子有限公司  
 SCONDAR ELECTRONIC LIMITED