



**SPECIFICATIONS**

Voltage Rating: 250V AC/DC  
 Current Rating: 2A AC/DC  
 Withstanding Voltage: 800V AC/minute  
 Insulation Resistance: 1000MΩ min.  
 Temperature Range: -25° C - +85° C  
 Contact Resistance: 20mΩ max

**TERMINAL**

Part No: SCT2011T  
 Wire Range: AWG#22-#28 (OD1.50mm)  
 Material: Phos. Bronze  
 Finish: Tin Plated  
 Thickness: 0.2mm  
 Q'TY: 10,000PCS/Reel

OPERATION	~ 10	±0.15	DRAW	JUDY	2006.05.09	SCALE	
DESIGN	20 ~ 30	±0.30	CHECK	MICKY	2006.05.09	UNIT	mm
ANGLE	30 ~	±0.50	APPROVE	HELLEN	2006.05.09	SIZE	A4
DIM	± 2'					SHEET	1/1
TOL						PROJ.	◆
CHANGE		APPROVE	PART NO.		SCT2011T		
MODIFICATION DESCRIPTION		NEW	TITLE:		DF11 2.0 Terminal		
REV	DATE	05/12/27	DRAWING NO.		SCT2011		

**SCONDAR** 森康达电子有限公司  
 SCONDAR ELECTRONIC LIMITED