



SPECIFICATIONS
 Voltage Rating: 250V AC/DC
 Current Rating: 2A AC/DC
 Withstanding Voltage: 800V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

WAFER
 Part No: SCT2011WR-2XXXP
 Poles: 2x2-20
 Material: Nylon 66, UL94V-0
 Pin: Brass, Tin plated

PART NO.	Dimensions	
	A	B
SCT2011WR-2X02P	2.00	6.00
SCT2011WR-2X03P	4.00	8.00
SCT2011WR-2X04P	6.00	10.00
SCT2011WR-2X05P	8.00	12.00
SCT2011WR-2X06P	10.00	14.00
SCT2011WR-2X07P	12.00	16.00
SCT2011WR-2X08P	14.00	18.00
SCT2011WR-2X09P	16.00	20.00
SCT2011WR-2X10P	18.00	22.00
SCT2011WR-2X11P	20.00	24.00
SCT2011WR-2X12P	22.00	26.00
SCT2011WR-2X13P	24.00	28.00
SCT2011WR-2X14P	26.00	30.00
SCT2011WR-2X15P	28.00	32.00
SCT2011WR-2X16P	30.00	34.00
SCT2011WR-2X17P	32.00	36.00
SCT2011WR-2X18P	34.00	38.00
SCT2011WR-2X19P	36.00	40.00
SCT2011WR-2X20P	38.00	42.00

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	JUDY	SCALE	PART NO.	DRAWING NO.
0	05/12/27	NEW			~ 10 20 ~ 30 30 ~	DESIGN		mm	SCT2011WR-2XXXP	DF11 2.0 90C Wafer
					Angle DIM	CHECK	MICKY	1/1		
					± 2'	APPROVE	HELLEN	PROJ.		SCT2011

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED