



PART NO.	Dimensions	
	A	B
SCT2504WR-2P	2.50	5.00
SCT2504WR-3P	5.00	7.50
SCT2504WR-4P	7.50	10.00
SCT2504WR-5P	10.00	12.50
SCT2504WR-6P	12.50	15.00
SCT2504WR-7P	15.00	17.50
SCT2504WR-8P	17.50	20.00
SCT2504WR-9P	20.00	22.50
SCT2504WR-10P	22.50	25.00
SCT2504WR-11P	25.00	27.50
SCT2504WR-12P	27.50	30.00
SCT2504WR-13P	30.00	32.50
SCT2504WR-14P	32.50	35.00
SCT2504WR-15P	35.00	37.50

SPECIFICATIONS
 Voltage Rating: 250V AC/DC
 Current Rating: 3A AC/DC
 Withstanding Voltage: 1000V AC/minute
 Insulation Resistance: 1,000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING
 Part No: SCT2504WR-XXP
 Poles: 2-15
 Material: Nylon 66, UL94V-0
 Pin: Brass, Tin plated

OPERATION	~ 10	±0.15	DRAW	CHENA	2010.12.03	SCALE	mm	 森康达电子有限公司 SCONDAR ELECTRONIC LIMITED	
DESIGN	20 ~ 30	±0.30	CHECK	MICKY	2010.12.03	UNIT	A4		
ANGLE	30 ~	±0.50	CHECK	HELLEN	2010.12.03	SHEET	1/1	PART NO.	SCT2504WR-XXP
DIM	± 2'		APPROVE			PROJ.		TITLE:	JAE2.5 90C WAFER
DATE	05/12/27		CHANGE			DRAWING NO.			SCT2504
REV	0	NEW	MODIFICATION DESCRIPTION						