



SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 2A AC/DC
 Withstanding Voltage: 500V AC/minute
 Insulation Resistance: 800MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

TERMINAL

Part No: SCT2508MT
 Wire Range: AWG#22-#28 (OD1. 80mm)
 Material: Brass
 Finish: Tin Plated
 Thickness: 0. 2mm
 Q'TY: 10, 000PCS/Reel

OPERATION		DRAW		SCALE	
~ 10	±0.15	Judy Huang	2006/05/02	mm	
20 ~ 30	±0.30	DESIGN		UNIT	
30 ~	±0.50	CHECK	Micky Liu	SIZE	A4
Angle	± 2'	APPROVE	Hellen Li	SHEET	1/1
DIM	TOL		2006/05/02	PROJ.	
MODIFICATION DESCRIPTION		CHANGE APPROVE		PART NO.	
0	05/12/27	NEW		SCT2508MT	
REV	DATE			TITLE:	
1				Molex 5240 TERMINAL	
				DRAWING NO.	
				SCT2508	

森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED