



SPECIFICATIONS
 Voltage Rating: 250V AC/DC
 Current Rating: 3A AC/DC
 Withstanding Voltage: 1000V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

TERMINAL
 Part No: SCT2542T
 Wire Range: AWG#22-#26 (OD1.55mm)
 Material: Brass
 Finish: Tin Plated
 Thickness: 0.2mm
 Q'TY: 15, 000PCS/Reel1

OPERATION	~ 10	±0.15	DRAW	CHENA	2006.08.12	SCALE	mm	 森康达电子有限公司 SCONDAR ELECTRONIC LIMITED	
DESIGN	20 ~ 30	±0.30	CHECK	MICKY	2006.08.12	UNIT	A4		
CHEK	30 ~	±0.50	APPROVE	HELLEN	2006.08.12	SIZE	1/1	PART NO.	SCT2542T
ANGLE	± 2'					SHEET	1/1	TITLE:	AMP280358 TERMINAL
DIM	± 2'					PROJ.		DRAWING NO.	SCT2542

REV	0	05/12/27	NEW	MODIFICATION DESCRIPTION	CHANGE	APPROVE	DATE	1
REV	1							2
REV								3
REV								4
REV								5
REV								6
REV								7
REV								8
REV								9
REV								10