





SPECIFICATIONS
Voltage Rating: 250V AC/DC
Current Rating: 3A AC/DC
Withstanding Voltage: 1500V AC/minute
Insulation Resistance: 100MΩ min.
Temperature Range: -25° C - +85° C
Contact Resistance: 20mΩ max

WAFER
Part No: SCT2544WV-2*XXP
Poles: 6-40
Material: PBT, UL94V-0
Pin: Brass/Gold-flash or Tin plated
QTY: 1, 000PCS/Bag



Poles	Dimensions (mm)		
	A	B	C
6	5.08	10.12	8.12
8	7.62	12.66	10.66
10	10.16	15.20	13.20
12	12.70	17.74	15.74
14	15.24	20.28	18.28
16	17.78	22.82	20.82
18	20.32	25.36	23.36
20	22.86	27.90	25.90
22	25.40	30.44	28.44
24	27.94	32.98	30.98
26	30.48	35.52	33.52
28	33.02	38.06	36.06
30	35.56	40.60	38.60
32	38.10	43.14	41.15
34	40.64	45.68	43.68
36	43.18	48.22	46.22
38	45.72	50.76	48.76
40	48.26	53.30	51.30

						SCONDAR 森康达电子有限公司 SCONDAR ELECTRONIC LIMITED				
						SCALE	UNIT	mm	PART NO.	SC12544WV-2*XXP