



1.90±0.10
4.30±0.10
1.15±0.10

3.90±0.25
4.20±0.25
A-A

2.40±0.25
2.50±0.25
B-B

SPECIFICATIONS
 Voltage Rating: 250V AC/DC
 Current Rating: 7A AC/DC
 Withstanding Voltage: 1500V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

TERMINAL
 Part No: SCT3962T
 Wire Range: AWG#18-#22 (OD3.2mm max)
 Material: BRASS
 Finish: Tin Plated
 Thickness: 0.25mm
 Q'TY: 5,000PCS/Reel

OPERATION	~ 10	±0.15	DRAW	CHENA	2005.03.13	SCALE	
	20 ~ 30	±0.30	DESIGN			UNIT	mm
	30 ~	±0.50	CHECK	MICKY	2005.03.13	SIZE	A4
Angle			APPROVE	HELLEN	2005.03.13	SHEET	1/1
DIM		± 2'				PROJ.	
DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE			DRAWING NO.	SCT3962
05/12/27	NEW					PART NO.	SCT3962T
						TITLE:	MOLEX5195 TERMINAL
						DRAWING NO.	SCT3962

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED