



SPECIFICATIONS
 Voltage Rating: 250V AC/DC
 Current Rating: 7A AC/DC
 Withstanding Voltage: 1500V AC/minute
 Insulation Resistance: 100MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING
 Part No: SCT5082H-XXP
 Pole: 02-12
 Material: Nylon 66, UL94V-2

PART NO.	Dimensions	
	A	B
SCT5082H-02P	5.08	10.68
SCT5082H-03P	10.16	15.76
SCT5082H-04P	15.24	20.84
SCT5082H-05P	20.32	25.92
SCT5082H-06P	25.40	31.00
SCT5082H-07P	30.48	36.08
SCT5082H-08P	35.56	41.16
SCT5082H-09P	40.64	46.24
SCT5082H-10P	45.72	51.32
SCT5082H-11P	50.80	56.40
SCT5082H-12P	55.88	61.48

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	CHECK	HELEN	SCALE	TITLE:
0	05/12/27	NEW			~ 10 ±0.15	DESIGN	MICKY	2005.03.13	A4	SCT5082H-XXP
					20 ~ 30 ±0.30	CHECK		2005.03.13	1/1	5.08 HOUSING
					30 ~ Angle ± 2'	APPROVE	HELLEN	2005.03.13		SCT5082

SCONDAR 森康达电子有限公司
 SCONDAR ELECTRONIC LIMITED