


A-A



B-B

SPECIFICATIONS

Voltage Rating: 250V AC/DC
 Current Rating: 10A AC/DC
 Withstanding Voltage: 1500V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

TERMINAL

Part No: SCT5083FT
 Wire Range: AWG#14-#22 (OD3. 3mm max)
 Material: Brass
 Finish: Tin plated
 Thickness: 0.25mmH
 Q' TY: 7, 000PCS/Reel

OPERATION		~ 10	±0.15	DRAW	JULIE	2016.11.14	SCALE	森康达电子有限公司 S'CONDAR ELECTRONIC LIMITED	
DESIGN		20 ~ 30	±0.30	CHECK	MICKY	2016.11.15	UNIT	mm	PART NO. SCT5083FT
CHECK		30 ~	±0.50	APPROVE	HELLEN	2016.11.15	SIZE	A4	
REV	DATE	MODIFICATION DESCRIPTION		CHANGE	APPROVE	DIM	Angle	SHEET	TITLE:
0	05/12/27	NEW				± Z	± Z	1/1	MOLEX8981 FEMALE Terminal
1						TOL	± Z	DRAWING NO.	SCT5083