


SPECIFICATIONS

Voltage rating: 250V AC, DC
 Current rating: 3A, AC, DC
 Withstanding Voltage: 1000V AC/minute
 Insulation resistance: 1000M Ω min
 Temperature range: -25 $^{\circ}$ C - +85 $^{\circ}$ C
 Applicable PC board thickness: 0.063" (1.6mm)
 Contact resistance: Initial Value/10m Ω max
 After environmental Texting/20m Ω

HOUSING

Part No: SCT41405FH-02P
 Material: Nylon 66 UL 94V-2
 Q'TY: 500, 1000 pcs/bag

OPERATION		DRAW		SCALE		 森康达电子有限公司 SCONDAR ELECTRONIC LIMITED			
~ 10	± 0.15	JUDY	2002.03.05	mm					
DESIGN									
20 ~ 30	± 0.30	CHECK	2002.03.05	A4	PART NO.	SCT4140FH-02P			
30 ~	± 0.50	APPROVE	2002.03.05	1/1	TITLE:	Molex41405 FEMALE HOUSING			
Angle	$\pm 2'$	hellen	2002.03.05	PROJ.	DRAWING NO.	SCT4140			
DIM	TOL								
1	2	3	4	5	6	7	8	9	10
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE					
0	05/12/27	NEW							