


**SPECIFICATIONS**

Voltage rating: 250V AC, DC  
 Current rating: 3A, AC, DC  
 Withstanding Voltage: 1000V AC/minute  
 Insulation resistance: 1000M Ω min  
 Temperature range: -25 °C - +85 °C  
 Applicable PC board thickness: 0.063 "(1.6mm)  
 Contact resistance: Initial Value/10m Ω max  
 After environmental Texting/20m Ω

**HOUSING**

Part No: SCT41405FH-2x02P  
 Material: Nylon 66 UL 94V-2  
 Q'TY: 500, 1000 pcs/bag

		OPERATION		DRAW		SCALE		 <b>森康达电子有限公司</b> SCONDAR ELECTRONIC LIMITED	
		~ 10	±0.15	DESIGN		UNIT	mm		
		20 ~ 30	±0.30	CHECK		SIZE	A4		
0	05/12/27	NEW		micky		SHEET	1/1	PART NO.	SCT4140FH-2x02P
REV	DATE	MODIFICATION DESCRIPTION		hellen		PROJ.	◆	TITLE:	Molex41405 FEMALE HOUSING
1				2002.03.05		DRAWING NO.	⇒		SCT4140
				2002.03.05					

1	2	3	4	5	6	7	8	9	10
				ANGLE	APPROVE				
				DIM					
				TOL					