


**SPECIFICATIONS**

Voltage rating: 250V AC, DC  
 Current rating: 3A, AC, DC  
 Withstanding Voltage: 1000V AC/minute  
 Insulation resistance: 1000M Ω min  
 Temperature range: -25 °C - +85 °C  
 Applicable PC board thickness: 0.063"(1.6mm)  
 Contact resistance: Initial Value/10m Ω max  
 After environmental Texting/20m Ω

**HOUSING**

Part No: SCT4140MH-2x2P  
 Material: Nylon 66 UL 94V-2  
 Q'TY: 500, 1000 pcs/bag

OPERATION		DRAW		SCALE		 <b>森康达电子有限公司</b> SCONDAR ELECTRONIC LIMITED			
~ 10	±0.15	DESIGN	judy	UNIT	mm				
20 ~ 30	±0.30	CHECK	micky	SIZE	A4				
30 ~	±0.50	CHECK	hellen	SHEET	1/1	PART NO.	SCT4140MH-2x2P		
Angle	± 2'	APPROVE	hellen	PROJ.	◆	TITLE:	AMP172165-1 MALE HOUSING		
DIM	TOL	APPROVE	hellen	2002.03.05	◆	DRAWING NO.	SCT4140		
DATE	DESCRIPTION	CHANGE	APPROVE	2002.03.05	◆	DRAWING NO.	SCT4140		
05/12/27	NEW								
REV	DATE	MODIFICATION	DESCRIPTION	CHANGE	APPROVE				
1									