



SPECIFICATIONS
 Voltage Rating: 250V AC/DC
 Current Rating: 8A AC/DC
 Withstanding Voltage: 1000V AC/minute
 Insulation Resistance: 1000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

HOUSING
 Part No: SCT28050FH-1x03P
 Material: Nylon 66, UL94V-0

OPERATION		DRAW		SCALE		森康达电子有限公司 SCONDAR ELECTRONIC LIMITED	
~ 10	±0.15	DESIGN	SIMON	UNIT	mm		
20 ~ 30	±0.30	CHECK	Micky.Liu	SIZE	A4	PART NO.	SCT28050FH-03P
30 ~	±0.50	APPROVE	Hellen.Li	SHEET	1/1	TITLE:	28050 FEMALE HOUSING
Angle	± 2'			PROJ.		DRAWING NO.	SCT28050
DIM	TOL						

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	SCALE	PART NO.
0	05/12/27	NEW			~ 10	DESIGN	mm	SCT28050FH-03P
					20 ~ 30	CHECK	A4	28050 FEMALE HOUSING
					30 ~	APPROVE	1/1	SCT28050
					Angle			
					DIM			